MIA(D)



TECHNICAL DATA SHEET

VERTICAL TYPE SERIES





AIM 14GF3

VERTICAL TYPE FREEZER - W/2 DOORS

- Designed to operate in 43°C ambient %65 humidity
- New design for equal temperature distribution
- Zero ODP Injected 42 kg/m3 Polyurethane Insulation
- Digital controller with easy read screen
- Ergonomic door and handle designed for ease of opening and cleaning
- Icecool refrigeration system designed to be most tecnologically advanced and energy efficient
- Hot gas defrost system
- Waste heat recovery condensate vaporiser system
- All refrigerators can be produced in marine version
- Marine version includes 'Icecool marine' system, legs and shelves















TECHNICAL DATA SHEET

Operating Tempatuare: -10/-22 °C

Climate class: 5 Capacity: 1340L

Overall dimensions: 1400x870x2100

CABINET CONSTRUCTION

Exterior Material: AISI 304 Stainless Steel

Back Material: Galvanized steel

Interior Material: AISI 304 Stainless Steel

Drain: ✓

LED lighting Eclairage LED: X

Insulation: Polyurethane with high density 40kg/m3, CFCs free, zero ODP and low GWP

Insulation thickness(mm): 60

Blowing Agent: HFO

Doors: 2

Door Construction: Pressed hinged door. Easy to replace door gasket that does not require

cleaning

Door Lock: Optional Door Frame Heaters: ✓

FEATURES

Shelving: 3x2

Shelves dimensions LxD: GN 2/1 650x530

Legs, casters: Stainless steel legs, heightadjustable (130-180mm)

REFRIGERATION

Thermostat: Touch screen- IP65 Refrigeration system: Split system

Defrost: Hot Gas

Expansion Device: Capillary

Fans: ✓

Condensation: Forced air Evaporation: With fan

Condensate pan: Resistance condensation pan

TECHNICAL FEATURES

Gas Refrigerant: R404A Charge de gas (gr): 1150

Power Supply: 230V / 1 / 50 Hz Refrigeration Capacity (W): 1075

Power (W): 860 Amps (A): 4

Energy Consumption (kWh/24h): 12

CRATING

Crated dimensions L x I x H (mm):1450x950x2350

Net Weight (kg): 190 Crated Weight (kg): 200











TECHNICAL DATA SHEET

NEW CONDENSER SYSTEM

Stayclear condenser





SAVING ENERGY

Eco friendly, HFC – free polyurethane insulation providing low energy consumption




EVAPARATOR DOES NOT SNOW THROUGH HOT GAS DEFROST





2100



PERFECT COOLING SYSTEM

Homogeneous heat distribution on each shelf thanks to custom design rear sheet



















