(D)AIM



TECHNICAL DATA SHEET

SPECIAL COLDLINE



AIM 70DRY DRY AGED REFRIGERATOR

- Designed to operate in 43°C ambient %65 humidity
- New design for equal temperature distribution
- Zero ODP Injected 42 kg/m3 Polyurethane Insulation
- Digital controller with easy read screen
- Ergonomic door and handle designed for ease of opening and cleaning
- Icecool refrigeration system designed to be most tecnologically advanced and energy efficient
- Hot gas defrost system
- Waste heat recovery condensate vaporiser system
- All refrigerators can be produced in marine version
- Marine version includes 'Icecool marine' system, legs and shelves

















TECHNICAL DATA SHEET

Antibacterial cooling with an activated carbon filter and an active UVC light

Stainless Steel Shelves

Humidity Control

Heated Glass

GENERAL INFORMATION

Operating Tempatuare: -3 / +5

Climate class: 5

Overall dimensions: 700x800x2100

Capacity: 610

CABINET CONSTRUCTION

Exterior Material: AISI 304 Stainless Steel

Back Material: Galvanized steel

Interior Material: AISI 304 Stainless Steel

Drain: ✓

LED lighting Eclairage LED: X

Insulation: Polyurethane with high density 40kg/m3, CFCs free, zero ODP and low GWP

Insulation thickness(mm): 50

Blowing Agent: HFO

REFRIGERATION

Thermostat: Touch screen-IP65 Refrigeration system: Split system

Defrost: Resistance

Expansion Device: Capillary

Fans: ✓

Condensation: Forced air **Evaporation:** With fan

Condensate pan: Hot gas condensation pan

TECHNICAL FEATURES

Gas Refrigerant: R134A

Power Supply: 230V / 1 / 50 Hz

CRATING

Crated dimensions L x l x H (mm):750x850x2350

Net Weight (kg): 129 Crated Weight (kg): 139



















TECHNICAL DATA SHEET


NEW CONDENSER SYSTEM

Stayclear condenser





EVAPARATOR DOES NOT SNOW THROUGH HOT GAS DEFROST



SAVING ENERGY

Eco friendly, HFC – free polyurethane insulation providing low energy consumption



