



TECHNICAL DATA SHEET

BAR SERIES COOLING LINE



BAR SERIES COOLING LINE AIM BB2

AIM BB2

BAR TYPE CHILLER - HINGED DOOR

- PVC coated galvanized steel.
- “CFC Free” refrigerant gas: R134A / R404A
- +32 °C ambient temp.
- Fan cooling.
- Digital thermometer and thermostat.
- Automatic defrosting.
- Lock system in the door.
- Special door hinge system.
- Removable and easy to clean magnetic door. - Hinged Doors.
- Working temperature: 2/10 °C





TECHNICAL DATA SHEET

Operating Temperature: +2/+10 °C
Capacity: 210L
Overall dimensions: 900x525x900

CABINET CONSTRUCTION

Exterior Material: Static paint
Back Material: Galvanized steel
Interior Material: AISI 304 Stainless Steel
Drain: ✓
LED lighting Eclairage LED: X
Insulation: Polyurethane with high density 40kg/m³, CFCs free, zero ODP and low GWP
Insulation thickness(mm): 50
Blowing Agent: HFO
Doors: 2
Door Construction: Pressed hinged door. Easy to replace door gasket that does not require cleaning
Door Lock: Optional
Door Frame Heaters: X

REFRIGERATION

Thermostat: Touch screen- IP65
Refrigeration system: Split system
Defrost: Resistance
Expansion Device: Capillary
Fans: ✓
Condensation: Forced air
Evaporation: With fan
Condensate pan: Hot gas condensation pan

FEATURES

Shelving: 1x2
Shelves dimensions LxD: 470x405
Legs, casters: Stainless steel legs, height adjustable (130-180mm)

TECHNICAL FEATURES

Gas Refrigerant: R134A
Power Supply: 230V / 1 / 50 Hz

CRATING

Crated dimensions L x l x H (mm):950x575x950
Net Weight (kg): 90
Crated Weight (kg): 100

NEW CONDENSER SYSTEM

Stayclear condenser



CLASSIC



AIMCLEAR

EVAPARATOR DOES NOT SNOW THROUGH HOT GAS DEFROST




CLASSIC



AIM-EVA

SAVING ENERGY

Eco friendly, HFC – free polyurethane insulation providing low energy consumption



BAR SERIES COOLING LINE AIM BB2

