(D)AIM



TECHNICAL DATA SHEET

BAR SERIES COOLING LINE





- Designed to operate in 43°C ambient %65 humidity
- New design for equal temperature distribution
- Zero ODP Injected 42 kg/m3 Polyurethane Insulation
- Digital controller with easy read screen
- Ergonomic door and handle designed for ease of opening and cleaning
- Icecool refrigeration system designed to be most tecnologically advanced and energy efficient
- Hot gas defrost system
- Waste heat recovery condensate vaporiser system
- All refrigerators can be produced in marine version

















TECHNICAL DATA SHEET

Operating Tempatuare: -2/+8 °C

Capacity: 140L

Overall dimensions: 600x640x820

CABINET CONSTRUCTION

Exterior Material: AISI 430 Stainless Steel

Back Material: Galvanized steel

Interior Material: AISI 430 Stainless Steel

Drain: ✓

LED lighting Eclairage LED: X

Insulation: Polyurethane with high density 40kg/m3, CFCs free, zero ODP and low GWP

Insulation thickness(mm): 50

Blowing Agent: HFO

Door: 1

Door Construction: Pressed hinged door. Easy to replace door gasket that does not require

cleaning

Door Lock: Optional Door Frame Heaters: X

FEATURES

Shelving: 1x2

Shelves dimensions LxD: 470x405 Legs, casters: Stainless steel legs, height adjustable (130-180mm)

REFRIGERATION

Thermostat: Touch screen- IP65 Refrigeration system: Split system

Defrost: Resistance

Expansion Device: Capillary

Fans: ✓

Condensation: Forced air **Evaporation:** With fan

Condensate pan: Hot gas condensation pan

TECHNICAL FEATURES

Gas Refrigerant: R134A

Power Supply: 230V / 1 / 50 Hz

CRATING

Crated dimensions L x I x H (mm): 650x690x1070

Net Weight (kg): 62 Crated Weight (kg): 72

















TECHNICAL DATA SHEET

NEW CONDENSER SYSTEM

Stayclear condenser





AIMCLEAR

SAVING ENERGY

Eco friendly, HFC – free polyurethane insulation providing low energy consumption



EVAPARATOR DOES NOT SNOW THROUGH HOT GAS DEFROST



















