(D) AIM



# TECHNICAL DATA SHEET

# **BAKERY COOLING LINE**



## AIM PR60R3

### VERTICAL TYPE PATISSERIE REFRIGERATOR -W/1 DOOR

- Designed to operate in 43°C ambient %65 humidity
- New design for equal temperature distribution
- Zero ODP Injected 42 kg/m3 Polyurethane Insulation
- Digital controller with easy read screen
- Ergonomic door and handle designed for ease of opening and cleaning
- Icecool refrigeration system designed to be most tecnologically advanced and energy efficient
- Hot gas defrost system
- Waste heat recovery condensate vaporiser system
- 22 no's of 40x60 tray capacity











(D) AIM



## TECHNICAL DATA SHEET

Operating Tempatuare: -2/+8 °C

Capacity: 610L

Overall dimensions: 700x870x2100

#### **CABINET CONSTRUCTION**

Exterior Material: AISI 304 Stainless Steel

Back Material: Galvanized steel

Interior Material: AISI 304 Stainless Steel

Drain: ✓

LED lighting Eclairage LED: X

Insulation: Polyurethane with high density 40kg/m3, CFCs free, zero ODP and low GWP

Insulation thickness(mm): 50

**Blowing Agent: HFO** 

Door: 1

Door Construction: Pressed hinged door. Easy to replace door gasket that does not require

cleaning

Door Lock: Optional Door Frame Heaters: X

### **CAPACITY**

22 pieces 40x60 tray capacity

#### REFRIGERATION

Thermostat: Touch screen- IP65 Refrigeration system: Split system

**Defrost:** Resistance

**Expansion Device: Capillary** 

Fans: ✓

Condensation: Forced air **Evaporation:** With fan

Condensate pan: Hot gas condensation pan

#### **TECHNICAL FEATURES**

Gas Refrigerant: R134A

Power Supply: 230V / 1 / 50 Hz

### **CRATING**

Crated dimensions L x l x H (mm):750x920x2350

Net Weight (kg): 124 Crated Weight (kg): 134















