(D) AIM



TECHNICAL DATA SHEET

BAKERY COOLING LINE



AIM PR70R4 VERTICAL TYPE PATISSERIE REFRIGERATOR -W/1 DOOR

- Designed to operate in 43°C ambient %65 humidity
- New design for equal temperature distribution
- Zero ODP Injected 42 kg/m3 Polyurethane Insulation
- Digital controller with easy read screen
- Ergonomic door and handle designed for ease of opening and cleaning
- Icecool refrigeration system designed to be most tecnologically advanced and energy efficient
- Hot gas defrost system
- Waste heat recovery condensate vaporiser system
- 22 no's of 60x80 tray capacity















TECHNICAL DATA SHEET

Operating Tempatuare: -2/+8 °C

Capacity: 730L

Overall dimensions: 775x1030x2100

CABINET CONSTRUCTION

Exterior Material: AISI 430 Stainless Steel

Back Material: Galvanized steel

Interior Material: AISI 430 Stainless Steel

Drain: ✓

LED lighting Eclairage LED: X

Insulation: Polyurethane with high density 40kg/m3, CFCs free, zero ODP and low GWP

Insulation thickness(mm): 50

Blowing Agent: HFO

Door Construction: Pressed hinged door. Easy to replace door gasket that does not require

cleaning

Door Lock: Optional Door Frame Heaters: X

CAPACITY

22 pieces 60x80 tray capacity

REFRIGERATION

Thermostat: Touch screen- IP65 Refrigeration system: Split system

Defrost: Resistance

Expansion Device: Capillary

Fans: ✓

Condensation: Forced air **Evaporation:** With fan

Condensate pan: Hot gas condensation pan

TECHNICAL FEATURES

Gas Refrigerant: R134A

Power Supply: 230V / 1 / 50 Hz

CRATING

Crated dimensions L x I x H (mm):825x1080x2350

Net Weight (kg): 160 Crated Weight (kg): 170















